



100% VISCOSE RAYON MULTICOLOR BROIDERY THREAD

Duravis Multicolor®

It is injection-dyed in up to four different colors to create a multi-colored effect on the thread. Duravis Multicolor adds a unique and eye-catching appearance to garments, ranging from subtle light-toned shades to bold rainbow contrasts.



Areas of Use

- **Broidery**
- **Apparel**
- **Home Textiles**
- **Underwear**

Product Properties

- Extra special look from light-toned shades to rainbow contrasting colors.
- Provides extra softness and comfort.
- Vivid and brilliant appearance.
- Injection-dyed in up to 4 colors.

Duravis Multicolor®

Storage Conditions

Must be stored away from heat, humidity and direct sunlight.

Points to consider

Embroidered products made with Visco are washable. However, in order to maintain color fastness, the following points should be observed during washing.

- 1- Embroidered items should be washed separately and not washed with other products.
- 2- They should not be placed tightly in the washing machine, as the embroidered items need to move freely inside the drum.
- 3- Embroidery products should be shaken immediately after washing, and should not be left folded or stacked when wet and damp.
- 4- Embroidered items (that do not contain chemical mixtures) should be washed with mild detergents. Harsh chemicals and bleach may cause discoloration of the embroidery.
- 5- Embroideries on woolen fabrics should not be machine washed and should not be shaken.
- 6- Stain removers or bleaching products should not be used.
- 7- Embroideries made of Viscose, can be applied with dry cleaning
- 8- Ironing should be done on the reverse of the embroidered surface or on another fabric. During ironing, use the lowest possible temperature and a steam iron instead of a damp cloth.
- 9- Due to environmental regulations and measures for nature protection, some materials used in dyes and paints are periodically changed. Therefore, despite all efforts, slight differences may occur between the color chart and the final product.

Thickness and Strength Chart

Ticket No.	Nominal Tex	Strength CN	Elongation %	Needle Size (Nm)
50/1*2	10	300	15 - 20	*
80/1*2	16	360	15 - 20	*
120/1*2	24	620	15 - 20	*

Color Fastness

Washing fastness at 60°C	ISO 105 C06	Min. 4
Water fastness	ISO 105 E01	Min. 4
Rubbing fastness	ISO 105 X12	Min. 4
Dry cleaning fastness	ISO 105 D01	Min. 4
Perspiration fastness	ISO 105 E04	Min. 4
Light fastness	ISO 105 B02	Min. 4

Product Options

Durak Duravis Multicolor® offers in a variety of meter sizes and thicknesses.

It is recommended to use low-melting interlining for mid and dark shade multicolor threads.

